# ALLSTRAP.com

Tel: (866) 779-2673

Fax: (614) 486-0510







P 328

**ORT 260** 

BXT3

# HIGH STRENGTH



5/8"x .035"x 4200' Polyester Strap

High quality, green polyester strapping for closing, reinforcing, and bundling materials for shipment, unitizing, palletizing, and bracing on standard light and mid weight loads. Exceeds ASTM D3950.

# **ALLSTRAP OPINION:**

This 1,300 pound break strength poly strap has replaced most 1/2", and 5/8" steel banding and generates major cost savings. PET is the least expensive for the break strength and performs great with battery powered tools like P 328, ORT 260 & BXT3. PET strap is strong, so you can pull high tension. It forms well to your load and will shrink (like a rubber band) if your load settles. PET is very good at absorbing shock.







1. Identification of Substance Product Identification: Polyester strapping - Black, White, Green Anchoring strap used for product shipping

CAS #z 25038-59-9 (98%)

Manufacturer/Supplier: Allstrap Steel & Poly Strapping Systems 1719 Kenny Road Columbus, OH 43212 (866) 779-2673

2. Hazards Identification
Under normal use conditions, this
product is non-hazardous. In it's solid
state, it presents no fire, explosion,
inhalation, ingestion Contact hazard.
Dust created from sanding, cutting, or
grinding should be treated as nuisance
dust and may cause irritation t0 the skin,
eyes and respiratory tract.

3. Composition/Data on Components CAS Chemical Name Percent 25038-59-9 Polyethylene terephthalate polymer (PET) 98%

### 4. First Aid Measures

Skin: In case of exposure to dust, wash with soap and Water. If Contact with molten resin occurs, affected area should be flushed with plenty of water. Seek medical attention for burns. Inhalation: In case of exposure to dust, remove to fresh air. Seek medical attention if irritation persists. Eyes: In case of exposure to dust, Flush eyes with water for at least 15 minutes. Seek medical attention if irritation persists. Ingestion: Not applicable.

5. Firefighting Measures
General Fire Hazards: Combustion
products are carbon, hydrogen and
oxygen. Molten
polymer can also produce
acetaldehyde.
Extinguishing Media: Class "A" or "B"
fire extinguishers or water fog.
Fire \_Fighting Equipment/instructions:
Wear positive-pressure, self-contained
breathing
apparatus with a full face piece and
protective clothing.

6. Accidental Release Measures

Strapping is in an inert form and emergency response is not needed.

### 7. Handling and Storage

Handling Procedures: No special handling requirements.
Storage Procedures: Do not store near potential ignition sources.

8. Exposure Controls and Personal Protection

Occupational Exposure Limits: No exposure limits established. Personal Protective Equipment: No personal protective equipment needed under normal handling. Wear NIOSH approved particulate respirator when dust is created. Engineering Controls: Engineering controls not needed.

9. *Physical and Chemical* Properties

Physical State: Solid, with or without wax Coating Odor: Odorless Flashpoint: Not determined Upper Flammability: Not determined

Lower Flammability: Not determined pH: Not applicable

Vapor Pressure: Not applicable Vapor Density: Not applicable Boiling Point: Not determined Melting Point: 260°C (500'1?)

Solubility (H20): Not soluble Specific Gravity: 1,334.45

Viscosity: Not applicable Evaporation Rate: Not applicable VOC: Not applicable Percent Volatile: 0 Freezing Point: Not applicable

10. Stability and Reactivity

Chemical Stability: Stable material, non-reactive.

Hazardous Decomposition: Not Applicable.

Hazardous Polymerization: Will not

Incompatible Materials: None. Conditions to Avoid: Storage near an ignition source.

11. Toxicological Information

Acute Toxicity: Not applicable. Skin Corrosion/Irritation: Product does not cause irritation. Serious Eye Damage/Irritation:

Product does not cause irritation. Respiratory or Skin Sensitization: Product does not cause irritation. Germ Cell Mutagenicity: Not determined. Carcinogenicity: Product is not classified as a carcinogen.
Component Carcinogenicity: Non-

carcinogenic.

Inhalation LCS() Rat: N/A Inhalation LCS() Mouse: N/A Oral LD50 Rat: N/A

Oral LD50 Mouse: NIA Dermal LD50 Rabbit:

N/A

Reproductive Toxicity: Product is not

Specific Target Organ Toxicity (STOT) Single Exposure: N/A STOT Repeated Exposure: N/A

Aspiration Hazard: No

Chronic Toxicity: No long term health hazards associated with polyethylene terephalate polymer.

12. Ecological Information

Ecotoxicity: No data available for this product.

13. Disposal Considerations

USEPA Waste Number and Descriptions: This product is not regulated as a hazardous waste under RCRA regulations.

Dispose of waste material according Local, State, Federal and Provincial regulations.

14. *Transport Information*US Federal Regulations: This product is not classified as a hazardous material for transport.

15. Regulatory Information

VVHMI: DSL, No components are listed in the WHMIS IDL. State Regulations: No information for product as a Whole. US Federal Regulations: No information for product as a whole.

Prepared 3/23/12 Revision 0

Key for Abbreviations and Acronyms Used:

LD50 Lethal oral dose for 50% of animals tested

LC50 = Lethal dose by inhalation for 50% of the animals tested.

WHMI = Canadian Workplace Hazards

and Materials Information

IDL = Canadian

"Ingredients Disclosure List"

DSL = Canadian "Domestic Substance List"

16.